

SmartGen 5.0

UECP COMPATIBLE RDS/RBDS ENCODER WITH LAN, USB & RS-232 CONNECTIVITY

The SmartGen 5 encoder has all the features you would ever need from an RDS encoder at a fantastic price. SmartGen 5 supports all RDS Applications in conformity with European CENELEC and United States NRSC standards and is fully compatible with UECP EBU SPB490 Version 7.05


The interactive function RT+ for song tagging is fully supported without a compromise. The SmartGen 5 can 'parse' scrolling text, automatically breaking phrases into word groups. Based on the latest RDS technology, the SmartGen 5 is fully digital design for 24/7/365 operation. The SmartGen 5 is cost effective solution for sending TMC and EWS Services. The front-panel LCD displays setup parameters without the need for an on-site computer, and also shows incoming raw data from station automation as well as exactly what the listener sees on his radio.

Supplied with free of charge, dedicated programming software "SmartGen RDS/RBDS Encoders Manager" this encoder programming is simple and foolproof like never before. SmartGen 5 comes along with Embedded WEB Server for remote and easy programming and supervision. SmartGen 5 gives dynamic programming access with its built-in RS232, USB, TCP/IP, UDP/IP interfaces. This connectivity permits full integration of RDS/RBDS transmissions with the station's other networked functions like message streams for Webcasting or Digital Radio. The SmartGen 5 encoder provides a full loopthrough interface for connection to your existing broadcast chain.

FEATURES

- Front panel LCD Display and Buttons for operating without a computer
- Remote configuration via ASCII or UECP through RS232, LAN, USB
- Supports European CENELEC and United States NRSC standards
- Displays outgoing scrolling messages exactly as seen by listener
- Includes the TA function for traffic message priority override
- Real time clock Schedules for Scrolling Text and text lists
- SNTP for automatic synchronization of the built-in clock
- Attractive price and very good price-performance ratio
- Fully compatible with UECP EBU SPB490 Version 7.05
- Internal data diagnostics and transmission safeguards
- Interfaces with all popular radio automation systems
- Compatible with EWS (Emergency Warning System)
- Proved and reliable hardware for 24/7/365 operating
- Embedded WEB server for interactive supervision
- Remote RDS viewer to visualize broadcasted data

- 4 General Purpose Outputs
- Easy Installation and Setup
- Built-in failsafe bypass relay
- LAN, USB & RS-232 Interfaces
- PS & Radio Text Scrolling Options
- Fully Digital Synthesis of RDS signal
- MPX Loopthrough & Sidechain Modes
- Supports TMC (Traffic Message Channel)
- Very Intuitive UECP Configuration Software
- 19" Professional Case for high RF immunity
- Supports RT+ for songs and content tagging
- Tally port for Traffic Announcement switching
- Internal or external Pilot / MPX synchronisation
- Works with any FM exciter and stereo generator
- Built-in dedicated 19kHz source for internal sync







SmartGen 5.0

SPECIFICATIONS

Technical Specifications		
Pilot/MPX Input	Yes	
MPX/RDS Output	0 to 4095 mV	
Inputs/Outputs	4 GPO, TA Input	
Communication Port	RS232, USB, LAN	
Synchronization External (Pilot or Mi	PX) / Internal / Auto	
Synchronization Monitoring	Yes	
RDS Level adjustment	Digitally controlled	
Phase adjustment	Yes, 0 ÷ 359.9°	
Separate outputs for RDS+MPX and for RDS only	No	
Command to activate the RDS SCA	Yes	
Side Chain Mode, Loop through mode, Bypass feature Yes		
RDS Subcarrier 100% Digitally Generated Shape / Bypass: 0 dB		
Pilot Sync Input Level: -50dBu to +12dBu / Frequency: 19kHz, ±3Hz		
EN50067 compliant	Yes	
Accurate Clock Time (CT) Sync with Internet Connection		
Remote TA actuation for Traffic Announcements Ye		
GPS module for automatic synchronization of the built-in clock N		
Fully independent RDS decoder for self-monitoring purposes N		
Firmware can be upgraded in the field Ye		
Front-panel LCD displays all programmed data	Yes	
Data may be entered on-site with Front-panel Butto	ns Yes	
Operating Temperature	-15°C ÷ 55°C	

Communication		
Communication Interfaces	RS232, USB,	LAN
Connection with Automati	on Software	Yes
Network Connectivity	2 TCP ports; 2 UDP p	orts
Scheduler		Yes
Configuration	Embeded Web Server, SmartGen Mana	ager
Password Protection		Yes
ASCII Protocol		Yes
UDP, TCP, HTTP, SNTP		Yes
Alert notifications on user-	-defined events via SNMP or E-mails	No
Embedded SNMP agent p	permitting active management tasks	No
Custom HTML formatted I	E-mail templates with dynamic variables	No
Supported Network Protoc	cols: HTTP, SNTP, UDP, TCP, U	PnP
UECP Protocol	Fully compliant with EBU SPB490 Ver.	7.05
PI <=> CALL Calculator		Yes
Remote Display		Yes

RDS Features	
Group supported	All
Group Sequence	Configurable
PS	6 DSN x 4 PSN
PI	6 DSN x 4 PSN
PTY	RDS/RBDS
AF Method A	25
AF Method B	up to 100
RT Yes	s, 10 messages
RT rate adjustment G	roup Sequence
RT+ for songs and content tagging	Yes
TP	Yes
TA Control Command, Contact clo	osure, Software
PTYN	Yes
EON	4 PSN
CT	Yes
TMC, EWS, IH, TDC	Yes
Free Format Groups (FFG)	Yes
Open Data Application (ODA)	Yes
64-character Dynamic PS shown on all RDS/RBDS Rad	dios Yes
Auto "parses" long messages for best text display	Yes
Scrolling by character	from 1 up to 8
Scrolling by word, Auto centering, Truncate long words	Yes

Operating conditions		
Temperature	-15°C to 55°C	
Humidity	< 95%, non-condensing	
Altitude	0 to 5000m above sea level	

Power	
Voltage	Internal, 115V or 230V
Power Consumption	10VA
Connector	IEC320, Fused and EMI-suppressed

Size and Weight	
Dimensions (W;H;D)	485 x 44 x 180 mm
Shipping Weight	540 x 115 x 300 mm / 2.445 kg
HS Code	8527212000



WE NEVER SPARE EFFORTS AND RESOURCES TO TURN OUR IDEAS INTO SUCCESSFUL PRODUCTS

